

SOIL

Rtt2

rear tine tiller

MECHANICAL REDUCER
chain + belt transmission



RUNNING SPEED

1.0 Km/h 1.1 Km/h

AMATEUR



Rtt2

	Euro	Euro	B&S	Honda
ENGINE	182.ohv 182 cc 3.1 kW Petrol	R210.ohv 212 cc 4.4 kW Petrol	CR950 208 cc 4.0 kW Petrol	GP160 163 cc 3.6 kW Petrol

STARTER recoil

HANDLEBAR	vertically adjustable	vertically adjustable	vertically and laterally adjustable	vertically and laterally adjustable
------------------	-----------------------	-----------------------	-------------------------------------	-------------------------------------

TRANSMISSION  gears, chain in oil bath and double belt system
1 fixed milling speed, reverse


ROTAVATOR 4 stars Ø32 cm - 16 riveted knives
work width 50 cm
270 rpm

OTHER adjustable spur
system for quick visual inspection of correct belt tensioning

DRIVE WHEELS tyres, tractor profile 13x5.00-6"
with mechanical transport idler

NET WEIGHT	65 kg	66 kg	67 kg	66.5 kg
-------------------	-------	-------	-------	---------

DIMENSIONS 53X116.5X70(h) cm

 GR.WEIGHT	71-73 KG
 PACKAGING	116,5X53X70(H) CM
PALLET	110X120X225(H) CM / Q* 6PCS



HANDLEBAR
vertically
and laterally adjustable*
* B&S / Honda only



TOOL COUPLING LEVER
with visual drive belt
tensioning control system



ROTAVATOR
riveted knives
Ø32 cm 50 cm



DRIVEN WHEELS
with mechanical
semi-differential



SMALL ROTAVATOR
cutter 32 cm
iron wheels Ø35x5



RIDGING PLOW
with fixed wings



AS STANDARD



OPTIONAL



PATENTED