

SOIL

Rtt3

rear tine tiller

MECHANICAL GEARBOX
chain + belt transmission



RUNNING SPEED

1.8 Km/h 2.1 Km/h
1.0 Km/h 1.1 Km/h



SEMIPROFESSIONAL



Rtt3

NEW!

ENGINE	Euro 212.ohv 212 cc 4.0 kW Petrol	Euro R210.ohv 212 cc 4.4 kW Petrol	B&S CR950 208 cc 4.0 kW Petrol	Honda GX160 163 cc 3.6 kW Petrol	Cramer/ greenworks 82 V 2.9 kW dual slot Elettrico
--------	---	--	--	--	--

STARTER recoil

HANDLEBAR	vertically adjustable	vertically adjustable	vertically and laterally adjustable	vertically and laterally adjustable	vertically and laterally adjustable
-----------	-----------------------	-----------------------	-------------------------------------	-------------------------------------	-------------------------------------

TRANSMISSION gears, chain in oil bath and double belt system
2 speed fixed milling, 2 speed reverse

TILLER 6 stars Ø32 cm - 20 bolted knives
work width 60 cm
270 rpm

OTHER adjustable spur system for quick visual inspection of correct belt tensioning

DRIVE WHEELS tyres, tractor profile 13x5.00-6"
with mechanical transport idler

NET WEIGHT	72 kg	72 kg	70.5 kg	70 kg	61 kg
------------	-------	-------	---------	-------	-------

DIMENSIONS 63x153x109(h) cm

GR.WEIGHT	75-77 KG
PACKAGING	116,5X53X70(H) CM
PALLET	110X120X225(H) CM / Q* 6PCS



HANDLEBAR
vertically and laterally
adjustable
* B&S / Honda /
Greenworks only



TOOL COUPLING LEVER
with visual drive belt
tensioning control system



ROTAVATOR
bolted knives
Ø32 cm 60 cm



DRIVEN WHEELS
with mechanical semi-
differential



SMALL ROTAVATOR
cutter 32 cm
iron wheels Ø35x5



RIDGING PLOW
with fixed wings



AS STANDARD



OPTIONAL



PATENTED